

GIPSFESTE

BELASTNING
Lett


2/12

Tillatt belastning i gips:

	Uttrekk kN	Skjær kN
Gipsfeste metall	0,08	0,27
Gipsfeste nylon	0,08	0,27
Gipsfeste Mini	0,05	0,15

1kN=100kg

Bruksmåte:



Varenr.	NOBB-nr.	GTIN-nr. (EAN)	Belegg/utførelse	Hodetype	Max feste	Skrue-dimensjon	Ant./F-pak (Forbr.pakn.)
---------	----------	----------------	------------------	----------	-----------	-----------------	--------------------------



Pozidriv PZ2

811110	21107875	7034358111104	Sink/El.forsinket	Panhode	1 - 12	4,2x38	100
811111	21107883	7034358111111	Sink/El.forsinket	Senkhode	1 - 27	4,2x45	100
811120	21107891	7034358111203	Nylon	Panhode	1 - 12	4,2x38	100
811121	21107909	7034358111210	Nylon, mini	Panhode	1 - 5	4,0x30	250

Fakta:

- ✓ Formonteres
- ✓ Spesialfeste for gips
- ✓ Skrutrekker er eneste verktøy
- ✓ Hurtig montering
- ✓ Økonomisk feste

Bruksområde:

Kun gips!

