BN
WALLCOVERINGS

AJ

Productsheet

Specifications		"ELEMENTS" Non-woven vinylwallcovering			
				Dimensions	Standard
Date	:	07-12-2011			
Application	:	Wallcovering.			
Type	:	Vinyl coating on a non woven backing.			
Packing	:	Each roll in shrinkfoil, 12 roll per cartonbox.			
Width of the roll	:	53		cm.	
Roll length	:	10,05		mtr	
Composition					
Total weight	:	235 +/- 50	#	g/m²	BN method 4200
Basematerial	:	90 +/- 5	#	g/m²	
Coating	:	145	#	g/m²	
Basematerial	:	Non woven			
Coating	:	Foamed PVC.			
# = Depends on design					
Other properties					
Flammability	:	European Class: B-s2-d0			EN 13501-1
Lightfastness	:	≥ 6 international woolscale			BS1006; ISO 105; DIN 54004
Washability	:	Scrubbable(*) (*) depends on structure.			EN 233 / EN 12956
Strippability	:	Strippable.			
Resistance against chemical influences					
Resistant to	:	Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.			
Not resistant to	:	Solvents like Ketones; Esters; Aromatic hydrocarbons.			
Application	:				
Wall	:	Dry, solid and free of grease			
Hanging	:	See roll label			
Adhesive	:	Methylan special for non woven or similar			

Quality Control Department

BN International BV
P.O Box 2 ; 1270AA Huizen ; The Netherlands
Tel. : 0031-35 5248439
Fax.: 0031-35 5234196
Mail: wallcovering@bnint.nl
Web.: www.bnwallcoverings.com

Productsheet

Specifications		"EYE" Non-woven vinylwallcovering			
				Dimensions	Standard
Date	:	12-09-2012			
Application	:	Wallcovering.			
Type	:	Vinyl coating on a non woven backing.			
Packing	:	Each roll in shrinkfoil, 12 roll per cartonbox.			
Width of the roll	:	53		cm.	
Roll length	:	10,05		mtr	
Composition					
Total weight	:	235 ± 40	#	g/m²	BN method 4200
Basematerial	:	85 ± 5	#	g/m²	
Coating	:	150	#	g/m²	
Basematerial	:	Non woven			
Coating	:	Foamed PVC.			
# = Depends on design					
Other properties					
Flammability	:	European Class : B-s2 -d0			EN 13501-1
Lightfastness	:	≥ 7 international woolscale			BS1006; ISO 105-B02; DIN 54004
Washability	:	Washable/ Scrubbable (*) (*) depends on design/structure.			EN 233 / EN 12956
Strippability	:	Strippable.			
Resistance against chemical influences					
Resistant to	:	Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.			
Not resistant to	:	Solvents like Ketones; Esters; Aromatic hydrocarbons.			
Application	:				
Wall	:	Dry, solid and free of grease			
Hanging	:	See roll label			
Adhesive	:	Methylan special for non woven or similar			

Quality Control Department

BN International BV
P.O Box 2 ; 1270AA Huizen ; The Netherlands
Tel. : 0031-35 5248439
Fax.: 0031-35 5234196
Mail: wallcovering@bnint.nl
Web.: www.bnwallcoverings.com

Productsheet

Specifications		"IMPULSE" Non-woven vinylwallcovering			
				Dimensions	Standard
Date	:	23-10-2013			
Application	:	Wallcovering.			
Type	:	Vinyl coating on a non woven backing.			
Packing	:	Each roll in shrinkfoil, 12 roll per cartonbox.			
Width of the roll	:	53		cm.	
Roll length	:	10,05		mtr	
Composition					
Total weight	:	205 Avg.	#	g/m²	BN method 4200
Basematerial	:	65 - 85 ± 5	#	g/m²	
Coating	:	125 Avg.	#	g/m²	
Basematerial	:	Non woven			
Coating	:	Foamed PVC.			
# = Depends on design					
Other properties					
Flammability	:	European Class : B-s2 -d0			EN 13501-1
Lightfastness	:	≥ 7 international woolscale			BS1006; ISO 105-B02; DIN 54004
Washability	:	Washable/ Scrubbable (*) (*) depends on design/structure.			EN 233 / EN 12956
Strippability	:	Strippable / Peelable.			
Resistance against chemical influences					
Resistant to	:	Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.			
Not resistant to	:	Solvents like Ketones; Esters; Aromatic hydrocarbons.			
Application	:				
Wall	:	Dry, solid and free of grease			
Hanging	:	See roll label			
Adhesive	:	Methylan special for non woven or similar			

Quality Control Department

BN International BV
P.O Box 2 ; 1270AA Huizen ; The Netherlands
Tel. : 0031-35 5248439
Fax.: 0031-35 5234196
Mail: wallcovering@bnint.nl
Web.: www.bnwallcoverings.com

AM

Productsheet

Specifications		"50 SHADES" Non-woven vinylwallcovering			
				Dimensions	Standard
Date	:	26-09-2013			
Application	:	Wallcovering.			
Type	:	Vinyl coating on a non woven backing.			
Packing	:	Each roll in shrinkfoil, 12 roll per cartonbox.			
Width of the roll	:	53		cm.	
Roll length	:	10,05		mtr	
Composition					
Total weight	:	200 ± 20	#	g/m²	BN method 4200
Basematerial	:	65 ± 5	#	g/m²	
Coating	:	135	#	g/m²	
Basematerial	:	Non woven			
Coating	:	Foamed PVC.			
# = Depends on design					
Other properties					
Flammability	:	European Class : B-s2 -d0			EN 13501-1
Lightfastness	:	≥ 7 international woolscale			BS1006; ISO 105-B02; DIN 54004
Washability	:	Washable/ Scrubbable (*) (*) depends on design/structure.			EN 233 / EN 12956
Strippability	:	Strippable / Peelable.			
Resistance against chemical influences					
Resistant to	:	Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.			
Not resistant to	:	Solvents like Ketones; Esters; Aromatic hydrocarbons.			
Application	:				
Wall	:	Dry, solid and free of grease			
Hanging	:	See roll label			
Adhesive	:	Methylan special for non woven or similar			

Quality Control Department

BN International BV AN
P.O Box 2 ; 1270AA Huizen ; The Netherlands
Tel. : 0031-35 5248439
Fax.: 0031-35 5234196
Mail: wallcovering@bnint.nl
Web.: www.bnwallcoverings.com

Productsheet

Specifications	"ORNAMENTALS" Non-woven vinylwallcovering			
			Dimensions	Standard
Date	: 14-03-2014			
Application	: Wallcovering.			
Type	: Vinyl coating on a non woven backing.			
Packing	: Each roll in shrinkfoil, 12 roll per cartonbox.			
Width of the roll	: 53		cm.	
Roll length	: 10,05		mtr	
Composition				
Total weight	: 220 ± 25	#	g/m²	BN method 4200
Basematerial	: 65 ± 5	#	g/m²	
Coating	: 155	#	g/m²	
Basematerial	: Non woven			
Coating	: Foamed PVC.			
# = Depends on design				
Other properties				
Flammability	: European Class : B-s2 -d0			EN 13501-1
Lightfastness	: ≥ 7 international woolscale			BS1006; ISO 105-B02; DIN 54004
Washability	: Washable/ Scrubbable (*) (*) depends on design/structure.			EN 233 / EN 12956
Strippability	: Strippable / Peelable.			
Resistance against chemical influences				
Resistant to	: Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.			
Not resistant to	: Solvents like Ketones; Esters; Aromatic hydrocarbons.			
Application	:			
Wall	: Dry, solid and free of grease			
Hanging	: See roll label			
Adhesive	: Methylan special for non woven or similar			

Quality Control Department

AH

HW

HOOKEDONWALLS®

Update 29 Jan 2014

SWEET LUXE

	Wallcovering		
Number of references	49		
Width	53 cm		
Length	10,05 m		
Repeat - vertical	33000-33009 (swanky medallion)	→|←	64 cm
	33050-33055 (sweet ornament)	→|←	64 cm
	33100-33103 (posh skin)	→|o	
	33150-33155 (mosaic de luxe)	→|←	2,37 cm
	33200-33206 (fancy croco)	→|←	64/32 cm
	33250-33265 (distorted textile)	→|o	
Repeat – horizontal	33000-33009 (swanky medallion)	53 cm	
	33050-33055 (sweet ornament)	21,33 cm	
	33100-33103 (posh skin)	53 cm	
	33150-33155 (mosaic de luxe)	2,37 cm	
	33200-33206 (fancy croco)	53 cm	
	33250-33265 (distorted textile)	53 cm	
Weight	33000-33009 (swanky medallion)	1,087 kg/r	204 g/m²
	33050-33055 (sweet ornament)	0,820 kg/r	154 g/m²
	33100-33103 (posh skin)	0,916 kg/r	172 g/m²
	33150-33155 (mosaic de luxe)	0,943 kg/r	177 g/m²
	33200-33206 (fancy croco)	0,911 kg/r	171 g/m²
	33250-33265 (distorted textile)	0,985 kg/r	185 g/m²
Packaging	12 rolls/box (except ref 33200 : 11 rolls/box and ref 33202 : 10 rolls/box)		
Composition	Non-woven		
Light resistance	6		
Origin	Made in E.C.		
Fire certificates	B S1 D0		
Tarif code	48149010		
Symbols			

A6

HW

HOOKEDONWALLS®

FROZEN FUSION

	Wallcovering		
Number of references	45		
Width	53 cm		
Length	10,05 m		
Repeat - vertical	82000-82004	→|←	32 cm
	82010-82023	→|o	
	82050-82055	→|←	32 cm
	82100-82106	→|←	1 cm
	82120-82124	→|←	16 cm
	82150-82157	→|←	32 cm
Repeat – horizontal	82000-82004	26,5 cm	
	82010-82023	53 cm	
	82050-82055	26,5 cm	
	82100-82106	1 cm	
	82120-82124	26,5 cm	
	82150-82157	26,5 cm	
Weight	82000-82004	0,948 kg/r	178 g/m²
	82010-82023	0,868 kg/r	163 g/m²
	82050-82055	1,172 kg/r	220 g/m²
	82100-82106	0,868 kg/r	163 g/m²
	82120-82124	1,001 kg/r	188 g/m²
	82150-82157	0,969 kg/r	182 g/m²
Packaging	12 rolls/box		
Composition	Non-woven (with waterbased ink)		
Light resistance	6		
Origin	Made in E.C.		
Fire certificates	B S1 D0		
Tarif code	48149010		
Symbols			

A1

HW

HOOKEDONWALLS®

PURE IMPULSE

	Wallcovering		
Number of references	47		
Width	53 cm		
Length	10,05 m		
Repeat - vertical	21500-21506	→|← 21,34 cm	
	21510-21514	→|← 64 cm	
	21520-21526	→|← 64 cm	
	21530-21534	→|← 64 cm and	→|← 64/32 cm
	21540-21544	→|← 64 cm and	→|← 64/32 cm
	21550-21567 (plain)	→|o	
Repeat – horizontal	21500-21506	17,60 cm	
	21510-21514	26,50 cm	
	21520-21526	53 cm	
	21530-21534	53 cm	
	21540-21544	53 cm	
	21550-21567 (plain)	53 cm	
Weight	21500-21506	0,959 kg/r	180 g/m²
	21510-21514	0,842 kg/r	158 g/m²
	21520-21526	0,868 kg/r	163 g/m²
	21530-21534	0,799 kg/r	150 g/m²
	21540-21544	0,852 kg/r	160 g/m²
	21550-21567 (plain)	0,799 kg/r	150 g/m²
Packaging	12 rolls/box		
Composition	Non-woven (with waterbased ink)		
Light resistance	6		
Origin	Made in E.C.		
Fire certificates	B S1 d0		
Tarif code	48149010		
Symbols	Ref 21500-21526 :	Ref 21530-21567 :	