

TECHNICAL DATASHEET

EGGER MEGAFLOOR cork⁺ + integrated silenzio[®] underlay

with HDF swell stopp plus and glueless locking installation system

Plant BRILON



1. Product Description

PRODUCT CONSTRUCTION – MEGAFLOOR cork⁺ with integrated silenzio[®] underlay
Technology



Natural Product – variations or differences of the surface finish are possible and typical!

Glueless Locking System



JUST clic!

The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue.
Patented as JUST clic! EP 1 441 087 and EP 1 462 587

2. Characteristics and General Requirements

Characteristics	Test Method	Unit	LANEO®
Core Board	-	-	HDF swell stopp plus
Profile	-	-	JUST <i>clic!</i>
Areas of Application	 Use for the complete living area.		
Format	-	-	CLASSIC
Thickness of the Elements	in dependence with EN 14085	mm	8,0 (± 0,25)
Length of the Surface	in dependence with EN 14085	mm	1292,0 (max. ± 2,0)
Width of the Surface	in dependence with EN 14085	mm	193,0 (± 0,2)
Flatness of the Element length	in dependence with EN 14085	%	∪ konkav ≤ 0,50 ∩ konvex ≤ 1,00
Flatness of the Element width	in dependence with EN 14085	%	∪ konkav ≤ 0,10 ∩ konvex ≤ 0,15
Straightness of the Surface (Banana form)	in dependence with EN 14085	mm / m	≤ 0,30
Squareness of the Element	in dependence with EN 14085	mm	≤ 0,50
Height differences	in dependence with EN 14085	mm (length / width)	Average ≤ 0,15 Single value ≤ 0,20 (acceptable)
Subfloor Heating System			
warm water based systems	-	-	Yes
Thermal Resistance	EN 12667	(m² K)/W	0,08
Sound Effect			
Impact Sound Reduction	EN ISO 140-8	ΔLw in dB	14
Room Sound Reduction	IHD W 431	Sone	14 (= 50% lower than the reference)
Light Fastness			
Blue Wool Scale B02	EN 20105	-	≥ level 6
Grey Wool Scale A02	EN 20105	-	≥ level 4
Formaldehyde Emission	EN 717	-	E 1
Flame Resistance	EN ISO 11925 - 2	-	Cfl- s1
Resistance to Staining	EN 423	with disinfectant with white spirit with ethyl alcohol with ammonia water	Level 0
		with iodine	Level 3
Effect of furniture leg	EN 424	tested with foot type 0	no damages
Static Indentation	EN 433	-	≤ 0,07
Guarantee Domestic	Acc. to EGGER cork + Guarantee condition	-	15 Years