

BN

Product- and Environmental Declaration #SMALLTALK

References

219200 - 219322

Product

Wallcoverings made of coated nonwoven with a weight of 1256 gr.
Roll length 10.05 x 0.53 m.

Enviromental mark

The wallcoverings are FSC® certified. FSC-C100728.

The BN wallcoverings are CE-marked and fulfils the enviromental demands according to product standard EN 15102:2007 + A1:2011. Declaration number: DOP-6.

Our wallcovering fulfils the product demands of emissions according to French VOC (Volatile Organic Compounds) Regulation DEVL 1104875A. Emmisions dans l'air interieur. Class: A+.

Our wallcoverings have the IGI (International Wallcovering Manufactor Association) Quality Mark Certificate. Our products fulfils the IGI's trade standards.

www.igiwallcoverings.org/industry-standards

Product Contents

All wallcoverings are free from heavy metals and other environmental harmful substances. All inks are water based.
Coatings are water based or PVC plastisol.

Fireclass

The BN wallcoverings have a fire class B-S1,d0, according to EN13501-1.

Usage

The wallcoverings can be used in all areas except wet areas such as bathrooms etc.

Colour fastness to light

Very good colour fastness to light 6 or better. The highest value is 8.

Transport

The wallcoverings are transported via trucks from our BN factory in Huizen, the Netherlands.

Care Instructions

The wallcoverings are extra washable. Stains are treated as follows:

- Wet the stain with a cloth or a sponge using soapy water or detergent.
- Use plenty of lukewarm water to get off all soap rests.
- Wipe off the over amount of water and leave the wallcovering to selfdry.
- Avoid to get water in the joints where the wallcoverings is unprotected.

Estimated lifetime

Estimated lifetime of the wallcoverings is 5 - 7 years.

Hanging Instructions

- Check the material after having hung three lengths. We do not accept any claim in excess of the first three lengths applied.
- Check the product for possible defects before you start. Use only rolls with the same batch number on a wall. In case of claim enclose the information label and a sample. Labour costs will not be reimbursed.
- Be sure the wall is smooth, clean and dry.
- Use glue for a heavy high-quality type of vinyl. Ask your dealer for advice.
- Cut the strips to length. Wall height + 5 cm. For designs with a repeated pattern, keep the repeat height in mind.
- Spread the glue to the wall.
- Apply the dry length on the glue.
- Roll away the air bubbles with a rubber roller.
- Cut strips on the plinth off along a steel ruler.
- Immediately remove glue spots with a sponge and clean water.
- Strip off dry when renovating.





SYMBOLS



EXTRA AFWASBAAR
EXTRA WASHABLE
EXTRA WASCHBESTÄNDIG
LAVABLE SUPPLÉMENTAIRE
ADICIONAL LAVABLE



SCHROBVAST
SCRUBBABLE
SCHEUERBESTÄNDIG
LESSIVABLE ET BROSSABLE
LEJABLE



ZEER GOEDE LICHTBESTENDIGHEID
VERY GOOD LIGHTFASTNESS
SEHR GUTE LICHTBESTÄNDIGKEIT
TRÈS BONNE RÉSISTANCE À LA LUMIÈRE
MAXIMA RESISTENCIA A LA LUZ



UITSTEKENDE LICHTBESTENDIGHEID
EXCELLENT LIGHTFASTNESS
AUSGEZEICHNETE LICHTBESTÄNDIGKEIT
EXCELLENTE RÉSISTANCE À LA LUMIÈRE
EXCELENTE RESISTENCIA A LA LUZ



DROOG AFSTRIPBAAR
DRY STRIPPABLE
RESTLOS ABZIEHBAR
ARRACHABLE À SEC
PARA QUITAR EL PAPAL, ARRANQUELO EN SECO



GEEN RAPPORT
FREE MATCH
ANSATZFREI
RACCORD LIBRE
SIN CASE



RECHT RAPPORT
STRAIGHT MATCH
GERADER ANSATZ
RACCORD DROIT
CASE RECTO



VERSPRINGEND RAPPORT
OFFSET MATCH
VERSETZTER ANSATZ
RACCORD SAUTÉ
CASE ALTERNO

32 cm

RAPPORT HOOGTE
DESIGN REPEAT/DISTANCE OFFSET
MUSTERHÖHE/VERSATZ
HAUTEUR DU RACCORD/DÉCALAGE
DISTANCIA DEL CASE



STORTEND VERWERKEN
REVERSE ALTERNATE LENGHTS
GESTÜRZT KLEBEN
INVERSER LES LÈS
INVERTIR PLIEGOS



VERWERKINGSRICHTING
IN PFEILRICHTUNG TAPEZIEREN
STRAIGHT HANG
SENCE DE LA POSE
DIRECCIÓN DE APLICACION

10,05 x 0,53m

ROLAFMETING
ROLL SIZE
ROLLENMAS
DIMENSIONS DE ROULEAU
DIMENSIONES



MUUR INLIJMEN
PASTE THE WALL
DIE WAND EINKLEISTERN
ADHÉSIF SUR LE MUR
ENCOLADO DE PARED