

# BN

## Product- and Environmental Declaration #SMALLTALK

### References

219200 - 219322

### Product

Wallcoverings made of coated nonwoven with a weight of 1256 gr.  
Roll length 10.05 x 0.53 m.

### Enviromental mark

The wallcoverings are FSC® certified. FSC-C100728.

The BN wallcoverings are CE-marked and fulfils the enviromental demands according to product standard EN 15102:2007 + A1:2011. Declaration number: DOP-6.

Our wallcovering fulfils the product demands of emissions according to French VOC (Volatile Organic Compounds) Regulation DEVL 1104875A. Emmisions dans l'air interieur. Class: A+.

Our wallcoverings have the IGI (International Wallcovering Manufactor Association) Quality Mark Certificate. Our products fulfils the IGI's trade standards.

[www.igiwallcoverings.org/industry-standards](http://www.igiwallcoverings.org/industry-standards)

### Product Contents

All wallcoverings are free from heavy metals and other environmental harmful substances. All inks are water based.  
Coatings are water based or PVC plastisol.

### Fireclass

The BN wallcoverings have a fire class B-S1,d0, according to EN13501-1.

### Usage

The wallcoverings can be used in all areas except wet areas such as bathrooms etc.

### Colour fastness to light

Very good colour fastness to light 6 or better. The highest value is 8.

### Transport

The wallcoverings are transported via trucks from our BN factory in Huizen, the Netherlands.

### Care Instructions

The wallcoverings are extra washable. Stains are treated as follows:

- Wet the stain with a cloth or a sponge using soapy water or detergent.
- Use plenty of lukewarm water to get off all soap rests.
- Wipe off the over amount of water and leave the wallcovering to selfdry.
- Avoid to get water in the joints where the wallcoverings is unprotected.

### Estimated lifetime

Estimated lifetime of the wallcoverings is 5 - 7 years.

### Hanging Instructions

- Check the material after having hung three lengths. We do not accept any claim in excess of the first three lengths applied.
- Check the product for possible defects before you start. Use only rolls with the same batch number on a wall. In case of claim enclose the information label and a sample. Labour costs will not be reimbursed.
- Be sure the wall is smooth, clean and dry.
- Use glue for a heavy high-quality type of vinyl. Ask your dealer for advice.
- Cut the strips to length. Wall height + 5 cm. For designs with a repeated pattern, keep the repeat height in mind.
- Spread the glue to the wall.
- Apply the dry length on the glue.
- Roll away the air bubbles with a rubber roller.
- Cut strips on the plinth off along a steel ruler.
- Immediately remove glue spots with a sponge and clean water.
- Strip off dry when renovating.



BN  
imagine what your wall can do





# SYMBOLS



EXTRA AFWASBAAR  
EXTRA WASHABLE  
EXTRA WASCHBESTÄNDIG  
LAVABLE SUPPLÉMENTAIRE  
ADICIONAL LAVABLE



SCHROBVAST  
SCRUBBABLE  
SCHEUERBESTÄNDIG  
LESSIVABLE ET BROSSABLE  
LEJABLE



ZEER GOEDE LICHTBESTENDIGHEID  
VERY GOOD LIGHTFASTNESS  
SEHR GUTE LICHTBESTÄNDIGKEIT  
TRÈS BONNE RÉSISTANCE À LA LUMIÈRE  
MAXIMA RESISTENCIA A LA LUZ



UITSTEKENDE LICHTBESTENDIGHEID  
EXCELLENT LIGHTFASTNESS  
AUSGEZEICHNETE LICHTBESTÄNDIGKEIT  
EXCELLENTE RÉSISTANCE À LA LUMIÈRE  
EXCELENTE RESISTENCIA A LA LUZ



DROOG AFSTRIPBAAR  
DRY STRIPPABLE  
RESTLOS ABZIEHBAR  
ARRACHABLE À SEC  
PARA QUITAR EL PAPAL, ARRANQUELO EN SECO



GEEN RAPPORT  
FREE MATCH  
ANSATZFREI  
RACCORD LIBRE  
SIN CASE



RECHT RAPPORT  
STRAIGHT MATCH  
GERADER ANSATZ  
RACCORD DROIT  
CASE RECTO



VERSPRINGEND RAPPORT  
OFFSET MATCH  
VERSETZTER ANSATZ  
RACCORD SAUTÉ  
CASE ALTERNO

32 cm

RAPPORT HOOGTE  
DESIGN REPEAT/DISTANCE OFFSET  
MUSTERHÖHE/VERSATZ  
HAUTEUR DU RACCORD/DÉCALAGE  
DISTANCIA DEL CASE



STORTEND VERWERKEN  
REVERSE ALTERNATE LENGHTS  
GESTÜRZT KLEBEN  
INVERSER LES LÈS  
INVERTIR PLIEGOS



VERWERKINGSRICHTING  
IN PFEILRICHTUNG TAPEZIEREN  
STRAIGHT HANG  
SENCE DE LA POSE  
DIRECCIÓN DE APLICACION

10,05 x 0,53m

ROLAFMETING  
ROLL SIZE  
ROLLENMAS  
DIMENSIONS DE ROULEAU  
DIMENSIONES



MUUR INLIJMEN  
PASTE THE WALL  
DIE WAND EINKLEISTERN  
ADHÉSIF SUR LE MUR  
ENCOLADO DE PARED