

**PAINT AND
VARNISHES
APPLIED AT SITE**

Self-declaration that the named products comply with the requirements for paint and varnishes applied at site as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the **MANUFACTURER** of paint and varnishes applied at site.

Approved emission certificates are M1¹, EC 1² or SINTEF Technical approval.

If the product has one of the approved emission certificates, it is not necessary to fill in this form. Connect the emission certificate to the product in goBIM.

¹ Approved performance standard NS-EN 15251:2007, Appendix C

² Approved performance standard GEV Emicode

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. **Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.**

| | |
|----------------------------|-----------------------------------|
| MANUFACTURER: | Osmo Holz und Color GmbH & Co. KG |
| PRODUCT TRADE NAME: | Osmo Hardwax Oil Original |
| PRODUCT ID: | 3062 Clear Matt for Flooring |
| INTENDED USE: | 3062 Clear Matt for Flooring |

The following is hereby confirmed by the manufacturer:

1. Interior paint and varnishes for walls, floors and ceilings applied at site and defined as category a, b, i or j acc. to directive 2004/42/CE, Annex, has undergone an emission test³ which shows that its emissions are below the values⁴ shown in table 15.

Table 15: Emission limits for all product categories – Conversion table


| Ref | Wall | | Floor/ceiling | | Sealants | |
|------------------|--------|--------|---------------|--------|----------|--------|
| | µg/m²h | µg/m³h | µg/m²h | µg/m³h | µg/m²h | µg/m³h |
| TVOC 28d | 200 | 417 | 200 | 160 | 4260 | 60 |
| Formaldehyde 3d | 24 | 50 | 62,5 | 50 | 3550 | 50 |
| Formaldehyde 28d | 50 | 104 | 50 | 40 | 710 | 10 |
| Carcinogenic | 5 | 10 | 5 | 4 | 71 | 1 |

³Documentation (test in acc. with approved standard) can be requested if required.

⁴Show accordance with units µg/m³ or µg/m²h

2. The emission test has been performed in accordance with the following approved standards ISO 16000-9 (or ISO 16000-10), ISO 16000-6 (volatile organic compounds) and ISO 16000-3 (formaldehyde).

Legally responsible: Mr. Chr. Cordes Position: Managing Director Date: 19/06/18

Signature: 
 osmo Holz und Color
 GmbH & Co. KG
 Gruppen Esch 12
 49231 Warendorf