

TEKNISK DATABLAD

AQUARELLE VÅTROMSGULV 3m

TopClean PUR-forsterket

(Kolleksjon 2016 - 2017)

September 2016

Gulvtype

EN 649

Vinylgulv

Bruksklasse

EN 685



23



32



41

Klasse



EN 428

Total tykkelse

2,00 mm



EN 429

Slitesjikt

0,40 mm



EN 426

Dimensjon

**15 - 25 m
3m**



EN 430

Total vekt

2,150 kg/m²



EN 660-2

Slitasjegruppe

T



EN 433

Inntrykksmerker

≤ 0,10 mm

Annen informasjon



ISO 105/B02

Lysbestandighet

≥ 6



EN 13501-1

Brannklasse

Bfl-s1



EN 12524

Varmemotstand

0,02 m²/kW



EN 13893

DIN 51130

Sklihemming

**≥ 0,30 μ
R9**



EN 1815

Statisk oppladning

≤ 2 kV



EN 13553

Vanntetthet


Godkjent



Aquarelle Floor 3m

0131-0005-DoP-2013-07
www.tarkett.se

Made by: Tarkett GDL SA.
Lentzweiler - LUXEMBURG



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.