

TECHNICAL DATA KÄHR'S LUXURY TILES






Click Herringbone 120 x 720 x 5 x 0.55 mm
1.04 m²/box, 98 box/pallet

PRODUCT











Click LVT Rigid Core SPC	EN ISO 10582	Luxury Vinyl Tile
Joint		Click 5Gi
Application	EN ISO 10874	23/33/42



SPECIFICATION

Thickness		EN ISO 24337	5.0 mm
Weight		EN ISO 24342	9.58 kg/m ²
Wear layer		EN ISO 24346	0.55 mm

PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, FloorScore, A+
Fire resistance	 EN 13501-1	Bfl-s1
Residual indentation	 EN ISO 24343-1 (2,5 h)	< 0.1 mm
Dimensional stability	 EN ISO 23999 (80 °C/6 h)	< 0.1 %
Colour fastness	 EN ISO 105-B02	≥ 6
Slip resistance	 EN 13893 DIN 51130	DS (> 0.3) R10
Electrical propensity	 EN 1815	< 2 kV (antistatic)
Wear and scratch resistance	 EN 16094	Pass with good results
Chemical resistance	 EN ISO 26987	Pass with good results
Effect of castor chair	 EN 425	Suitable
Underfloor heating		Ok (max +27 °C)
Bacterial growth		Does not act as substrate

Cleaning and maintenance instructions, see: www.kahrs.com

