

## EU Type Examination Certificate

Date: 2020/01/23

n. **700200401/OE**

Validity:  
2025/01/22

This document cancels the previous one nr. 700174103/OE dated 2017/10/13

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	<b>MASPICA SPA</b> Via Einstein, 6 – 35020 Casalserugo (PD) – Italia
Type of PPE:	<b>Safety footwear</b> in conformity with <b>EN ISO 20345:2011 class I</b> (= footwear in leather and other materials)
Category of PPE:	<b>II</b> : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model	<b>"ORTISEI MC"</b> Line ST30 SCOUT

Description:



design: B (ankle footwear);  
fastening system: by means of laces;  
processing: direct injection;  
sole: black and green rubber (code ST30 SCOUT) marked SRC Made in Italy Vibram;  
midsole: black color PU foam;  
upper: black coated calf (cow) leather (code PE PUK806) declared 1,8-2,0 mm thick with lateral inserts in black microfiber (code TE MCG800) declared 1,8 mm thick and grey fabric PA+PE (code TE VECF351); in the heel region there is an insert in yellow reflective material (code RI REFL455);  
collar: the same fabric of the upper matched with MTP 3,5 mm (code TE VECM351);  
tongue/bellows: black full grain leather (cow) (code PE FION802) declared 1,0-1,2 mm thick, lined and centrally padded;  
vamp and quarter lining: black three-dimensional fabric article AERPLUS BZB (PL) (code FO RET800);  
tongue lining: yellow-fluo three-dimensional fabric article AERPLUS BZB (PL) (code FO RET404);  
heel-grip: black microsuede PU-PA declared thickness 0,8/1,0 mm (code FO MCT800);  
insole: multilayered fabric article KK7 by FF Srl Lenzi (code SO KVL009) and alternatively multilayered fabric article T-427 by Texon Italia (code SO KVL035), which also serves as penetration resistant insert;  
removable insock: light blue EVA matched with orange knitted fabric marked Sixton Blow-fit 2.0 on the foot side and grey fabric on the lower side, with grey latex insert in the heel area on the lower side (code SU TERDF01);  
toecap: aluminum toecap article A159 Alustrategy (code PT A0159A).

Optional interchangeable orthopedic insocks (DGUV 112-191): **SECOSOL®** by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 3,14mm):

- "Complete" code 951622012451XX;
  - "Einlagen-Bausatz mit EVA-decke" code 9516101XXX5XXX;
  - "Einlagen-Bausatz mit textile-decke" code 9516101XXX7XXX;
- by ARNEPLANT (max thickness in the toetip area: 3,15mm):
- "low arch support (green)" code ACC-SUCAL01;
  - "medium arch support (blue)" code ACC-SUCAM01;
  - "high arch support (red)" code ACC-SUCAH01.

## EU Type Examination Certificate

Date: 2020/01/23

n. **700200401/OE**

Validity:  
2025/01/22

Technical Standard: **EN ISO 20344:2011** Personal protective equipment – Test methods for footwear  
(UNI EN ISO 20344:2012)  
**EN ISO 20345:2011** Personal protective equipment – Safety footwear  
(UNI EN ISO 20345:2012)

Intended use: general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.

Size range: from 38 to 48

Technical File: **DC-11733/E**

Test report: **RCT n°3815108/E**

Functions and performance levels: **basic requirements for safety footwear (SB)** (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

**SRC = Slip resistance** – meets the following requirement:

- surface: ceramic / lubricant: detergent solution;
- surface: steel / lubricant: glycerol.

**Additional requirements** (Tab.18 and 20 of EN ISO 20345:2011):

**S3** = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; **WR** = water resistance of the whole footwear; **HRO** = resistance to hot contact of the outsole; **HI** = heat insulation of sole complex; **CI** = cold insulation of sole complex.

Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

Marking: on a stitched label and displaying the following information:

- **CE Marking**;
- Name of the Manufacturer + complete address;
- designation of the footwear (alphanumeric code, unique/unambiguous);
- Standard of Reference + safety symbols;
- size of the footwear (printed on the outsole);
- date of production;
- additional information: internal codes.



# EU Type Examination Certificate

Date: 2020/01/23

n. **700200401/OE**

Validity:  
2025/01/22



**SECOSOL®**  
"Complete"  
code 951622012451XX



**SECOSOL®**  
"Einlagen-Bausatz mit EVA-Decke"  
code 9516101XXX5XXX



**SECOSOL®**  
"Einlagen-Bausatz mit Textil-Decke"  
code 9516101XXX7XXX



"Low arch (green)"  
code ACC-SUCAL01



"Medium arch (blue)"  
code ACC-SUCAM01



"High arch (red)"  
code ACC-SUCAH01



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

