

INFORMAZIONI TECNICHE
TECHNICAL FEATURES / INFORMATIONS TECHNIQUES / TECHNISCHE INFORMATIONEN / INFORMACIÓN TÉCNICA

DESCRIZIONE DESCRIPTION / DESCRIPTION BESCHREIBUNG / DESCRIPCIÓN	NORME REGULATION / NORME / NORM / NORMA EN 14411 - ISO 13006	REQUISITI PRESCRITTI REQUIRED VALUES / EXIGENCES RÉGLEMENTAIRES / VORGESCHRIEBENE ANFORDERUNGEN / REQUISITOS ESTABLECIDOS	VALORI VALUES / VALEURS WERTE / VALORES		
 DIMENSIONI RETTIFICATO SIZES RECTIFIED / FORMAT RECTIFIÉ / ABMESSUNGEN NACH DEM SCHLEIFEN / TAMAÑO RECTIFICADO	UNI EN ISO 10545-2	lunghezza-larghezza ±0,3% (±1,0 mm max) lenght-width / longueur-largeur / Länge-Breite / longitud-ancho	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME		
		spessore ±5,0% (±0,5 mm max) thickness / épaisseur / Stärke / espesor			
 DIMENSIONI NON RETTIFICATO SIZES NOT RECTIFIED / FORMAT NON RECTIFIÉ / ABMESSUNGEN VOR DEM SCHLEIFEN / TAMAÑO NO RECTIFICADO	UNI EN ISO 10545-2	ortogonalità ±0,3% (±1,5 mm max) rectangularity / orthogonali�� / Rechtwinkligkeit / ortogonalidad	-		
		rettilinearit�� ±0,3% (±0,8 mm max) straightness / rectilignit�� / Geradlinigkeit / rectilineidad			
 DIMENSIONI NON RETTIFICATO SIZES NOT RECTIFIED / FORMAT NON RECTIFI�� / ABMESSUNGEN VOR DEM SCHLEIFEN / TAMA�� NO RECTIFICADO	UNI EN ISO 10545-2	planarit�� ±0,4% (±1,8 mm max) surface flatness / plan���� / Ebenfl��chigkeit / planaridad	-		
		qualit�� superficie ��95% surface quality / qualit��s surface / Oberfl��chenbeschaffenheit / cualidades superficie			
 ASSORBIMENTO ACQUA WATER ABSORPTION / ABSORPTION D'EAU / WASSERAUFNAHME / ABSORCI��N DE AGUA	UNI EN ISO 10545-3	��0,5%	��0,1%		
 RESISTENZA A ROTTURA BREAKING STRENGHT / R��SISTANCE �� LA RUPTURE / BRUCHFESTIGKEIT / RESISTENCIA A LA ROTURA	UNI EN ISO 10545-4	R��35 N/mm�� S��700 N (<7,5 mm) S��1300 N (��7,5 mm)	6 mm	9 mm	20 mm
			R��40 N/mm�� S��1000 N	R��40 N/mm�� S��1500 N	R��45 N/mm�� S��10000 N
 RESISTENZA ABRASIONE PROFONDA (UGL - Matt) DEEP ABRASION RESISTANCE (UGL - MATT) / R��SISTANCE �� ABRASION PROFONDE (UGL - MATT) / TIEFENVERSCHLEISSBEST��NDIGKEIT (UGL - MATT) / RESISTENCIA A LA ABRASI��N PROFUNDA (UGL - MATT)	UNI EN ISO 10545-6	��175 mm��3	��150 mm��3		
			-		
 RESIST. ABRASIONE SUPERFICIALE (GL - Lappato / Silky) SURFACE ABRASION RESISTANCE (GL - LAPPATO / SILKY) / R��SIST. �� L'ABRASION SUPERFICIELLE (GL - ROD�� / SILKY) / WIDERST��NDIGKEIT GEGEN OBERFL��CHENVERSCHLEISS (GL - GEL��PPT / SILKY) / RESIST. ABRASI��N SUPERFICIAL (GL: ESMALTADO / SILKY)	UNI EN ISO 10545-6	dichiarare un valore / declare a value / d��clarer une valeur / einen Wert angeben / declarar un valor	-		
 RESISTENZA SHOCK TERMICI THERMAL SHOCK RESISTANCE / R��SISTANCE AUX ��CARTS DE TEMP��RATURE / WIDERSTANDSF��HIGKEIT GEGEN TEMPERATURSCHWANKUNGEN / RESISTENCIA A LOS CAMBIOS DE TEMPERATURA	UNI EN ISO 10545-9	resistenza / resistant / r��sistance / Widerst��ndigkeit / resistencia	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERF��LLT / CONFORME		
 RESISTENZA AL GELO FROST RESISTANCE / RESISTANCE AU GEL / FROSTWIDERSTANDSF��HIGKEIT / RESISTENCIA AL HIELO	UNI EN ISO 10545-12	resistenza / resistant / r��sistance / Widerst��ndigkeit / resistencia	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERF��LLT / CONFORME		
 RESISTENZA CHIMICA CHEMICAL RESISTANCE R��SISTANCE CHIMIQUE CHEMISCHE BEST��NDIGKEIT RESISTENCIA QU��MICA	UNI EN ISO 10545-13	resistenza / resistant / r��sistance / Widerst��ndigkeit / resistencia	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERF��LLT / CONFORME		
 RESISTENZA ALLE MACCHIE STAIN RESISTANCE / RESISTANCE AUX TACHES / FLECKENFESTIGKEIT / RESISTENCIA A LAS MANCHAS	UNI EN ISO 10545-14	pulibile / cleanable / nettoyyable / kann gereinigt werden / lavable	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERF��LLT / CONFORME		
 CLASSIFICAZIONE ANTISDRUCCIOLO ASSESSMENT OF SLIP RESISTANCE / CLASSIFICATION ANTIGLISSE RUTSCHFESTIGKEITSKLASSECLASIFICACI��N ANTIDESLIZANTE	DIN 51130	R	R9 120x278 - 120x120 - 60x120 - 30x120 - 80x80 - 60x60 - 30x60 - 9,7x60 R10 60x120 - 60x60 - 30x60 R11 60x90 K2 - 80x80 K2		
	DIN 51097	A+B+C	A Natural R9 A+B Structured R10 A+B+C Structured R11		
	B.C.R.A. (COF)	>0,40 bagnato / wet	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERF��LLT / CONFORME		
	ANSI A137.1 2012 (DCOF)	>0,42 bagnato / wet	CONFORME COMPLIANT / CONFORME ANFORDERUNGEN ERF��LLT / CONFORME		
 CLASSIFICAZIONE ANTISDRUCCIOLO ASSESSMENT OF SLIP RESISTANCE / CLASSIFICATION ANTIGLISSE RUTSCHFESTIGKEITSKLASSECLASIFICACI��N ANTIDESLIZANTE	BS 7976- 2:2002 (UK) (Pendulum Test Value)	0-24 scivoloso / slippery / glissant / Rutschig / resbaladizo 25-35 scivolosit�� moderata / moderately slippery / glissance mod��r��e / m���ige Rutschgefahr / Deslizamiento moderado >36 basso rischio scivolamento / low slipping risk / risque de glissement faible / geringe Rutschgefahr / bajo riesgo de deslizamiento	>36 60x120 - 60x60 - 30x60 White/Ivory/Gold/Avana		

Piastrelle pressate a secco - Conforme alla norma EN 14411 e ISO 13006 appendice G gruppo B1-a con E   0,5%

Dry pressed tiles - Compliant with standards EN 14411 and ISO 13006 annex G group B1-a with E   0,5% / Carreau press      sec - Conforme    la norme EN 14411 et ISO 13006 annexe g groupe B1-a avec E   0,5% / Trocken gepresste Fliesen - Erf  llen die Anforderungen der Norm en 14411 und ISO 13006 Anhang g Gruppe B1-a mit E   0,5% / Baldosas prensadas en seco - Conforme a las normas en 14411 e iso 13006, anexo g grupo B1-a con E   0,5 %